

6664/6AB4

High-Mu Triode

7-PIN MINIATURE TYPE
For Mobile-Communications Equipment

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Absolute-Maximum Values*):

Voltage (AC or DC) 6.3^a volts

Current at heater volts = 6.3 0.150 amp

Peak heater-cathode voltage:

Heater negative with
respect to cathode. 100 max. volts

Heater positive with
respect to cathode. 100 max. volts

Direct Interelectrode Capacitances (Approx.):

	<i>Without External Shield</i>	<i>With External Shield^b</i>	
Grid to plate	1.5	1.5	$\mu\mu\text{f}$
Grid to cathode and heater.	2.2	2.2	$\mu\mu\text{f}$
Plate to cathode and heater	0.5	1.4	$\mu\mu\text{f}$
Cathode to plate.	0.24	0.20 ^c	$\mu\mu\text{f}$
Cathode to grid and heater.	5.0	5.2 ^d	$\mu\mu\text{f}$
Plate to grid and heater.	1.7	2.6 ^d	$\mu\mu\text{f}$
Heater to cathode	2.9	2.9 ^c	$\mu\mu\text{f}$

Characteristics, Class A₁ Amplifier:

Plate Supply Voltage. 100 250 volts

Cathode Resistor. 270 200 ohms

Amplification Factor. 60 60

Plate Resistance (Approx.). 15000 10900 ohms

Transconductance. 4000 5500 μmhos

Plate Current 3.7 10 ma

Grid Voltage (Approx.)

for plate $\mu\text{a} = 10$ -5 -12 volts

Mechanical:

Operating Position. Any

Type of Cathode Coated Unipotential

Maximum Overall Length. 2-1/8"

Maximum Seated Length 1-7/8"

Length, Base Seat to Bulb Top (Excluding tip). . . 1-1/2" $\pm$ 3/32"

Diameter. 0.650" to 0.750"

Dimensional Outline See *General Section*

Bulb. T5-1/2

Base. Small-Button Miniature 7-Pin (JEDEC No. E7-1)




RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
5-62

6664/6AB4

Basing Designation for BOTTOM VIEW. 5CE

Pin 1 - Plate
Pin 2 - No Internal
 Connection
Pin 3 - Heater
Pin 4 - Heater



Pin 5 - No Internal
 Connection
Pin 6 - Grid
Pin 7 - Cathode

AMPLIFIER — Class A₁

Maximum Ratings, *Absolute-Maximum Values:*

PLATE VOLTAGE. 330 max. volts
GRID VOLTAGE:
 Negative-bias value. 55 max. volts
 Positive-bias value. 0 max. volts
PLATE DISSIPATION. 2.9 max. watts

^a When operated from storage-battery systems, the heater may be subjected to voltage variations as great as ± 20 per cent. Although such extremes in heater voltage may be tolerated for short periods, increased equipment reliability can be achieved with improved supply-voltage regulation.

^b With external shield JEDEC No.316 connected to cathode except as noted.

^c With external shield JEDEC No.316 connected to ground.

^d With external shield JEDEC No.316 connected to grid.

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling:

Cycles of Intermittent Operation 2000 min. cycles

This test is performed on a sample lot of tubes from each production run under the following conditions: heater volts = 7.5 cycled one minute on and one minute off, heater 135 volts positive with respect to cathode, and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Transconductance at Reduced Heater Voltage:

Average Value. 3200 μ mhos

With heater volts = 5.0, plate supply volts = 250, and cathode resistor (ohms) bypassed = 200.

